

MATERIAL SAFETY DATA SHEET

SANDLOCK ADDITIVE & PREMIX

ORGANIC JOINT SAND STABILIZER



*Always check our website at: WWW.SANDLOCK.NET
for the latest MSDS and application info!!*

SANDLOCK ADDITIVE

SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name:

SANDLOCK, L.L.C.
P.O. Box 746
Prior Lake, Minnesota 55372
Phone: (952) 226-6833
Fax: (952) 226-6806
Toll Free: (800) 241-9153

Name: SANDLOCK

Class:

CAS No.:

UN No.:

SECTION II - HAZARDOUS INGREDIENTS

Psyllium

SECTION III - PHYSICAL DATA

VOC:

VAPOR PRESSURE:

N/A

VAPOR DENSITY (air = 1.0):

SPECIFIC GRAVITY:

N/A

PERCENT VOLATILE BY VOLUME:

EVAPORATION RATE:

N/A

SOLUBILITY IN WATER:

Insoluble, Forms Mucilage

PH:

COEFFICIENT OF WATER/OIL DISTRIBUTION:

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:

NONE

LOWER EXPLOSIVE LIMIT:

UPPER EXPLOSIVE LIMIT:

EXTINGUISHING MEDIA:

Water, dry mixture fire extinguisher

SPECIAL FIREFIGHTING PROCEDURE:

Not normally necessary.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS:

dust concentrations in closed-in areas or compartments.

Treat like grain dust. Avoid high levels of

SENSITIVITY TO IMPACT:

None

SECTION V - HEALTH HAZARD DATA

IMMEDIATE EFFECTS (ACUTE and CHRONIC):

Not hazardous - may cause allergic reaction in those individuals sensitive to inhaled or ingested psyllium powder.

Majority of people will experience no adverse reactions when using this product for its intended purposes. Those with allergic reactions should take special care. Avoid high level of dust concentrations in closed-in areas or compartments.

Signs and Symptoms of Exposure: Excessive exposure may produce irritation of skin, eyes or respiratory tract.

Generally aggravated by Exposure: Allergies, asthma, bronchitis, emphysema, dermatitis.

DELAYED EFFECT:

FIRST AID PROCEDURES

EYES: Standard eye wash procedures, flush with water.

SKIN: Flush with water.

INHALATION: Remove victim to fresh air; if breathing is difficult, consult doctor.

INGESTION: Consult a physician.

POSSIBLE ROUTES OF ENTRY:

SECTION VI - REACTIVITY DATA

STABILITY:

HAZARDOUS DECOMPOSITION PRODUCTS: None known.

SECTION VII - SPILL OR LEAK PROCEDURES

RELEASE OF SPILL:

- Sweep/vacuum, dispose of in accordance with local, state and federal laws. Do not use water - material forms mucilaginous gel.

WASTE DISPOSAL:

- Solid waste disposal. Observe regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Non-toxic particle mask.

VENTILATION:

PROTECTIVE CLOTHING: Protective gloves, if subject to dermatitis, safety goggles, coveralls to protect clothing from excessive dusting.

SECTION IX - SPECIAL PRECAUTIONS

Store in tightly sealed containers. Do not get wet, use good housekeeping practices. Avoid breathing dust. Can cause damage to asphalt, so avoid mixing, staging or any contact with asphalt.

SAND (contained in SANDLOCK PREMIX)

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME: SAND

COMMON NAMES: Crystalline Silica in the form of quartz, silica Sand, Traction Sand

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Ingredient:	CAS No.:	OSHA PEL:	ACGIH TLV:
-------------	----------	-----------	------------

Silica, as quartz	14808-60-7	mg/m ³ 10/ (%SiO ₂ +2)	mg/m ³ 0.1
-------------------	------------	---	--------------------------

Exposure limits are for respirable fraction

Crystalline free silica, in the form of quartz, is present in these sands at a maximum level of 3% by weight. The proportion of the silica that is in the respirable size range (<10 μm particle size) varies and is always less than 0.015 percent of the total sand by weight.

NIOSH recommends a Permissible Exposure Limit (PEL) of 0.5 mg/m³ for respirable free silica.

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

PHYSICAL STATE: Solid

ODOR / APPEARANCE: Natural sand or rock particles (maximum size ½ inch), no distinctive odor

VAPOR PRESSURE: N/A

VAPOR DENSITY: N/A

EVAPORATION RATE: N/A

BOILING POINT: N/A

FREEZING POINT: N/A

pH in WATER: Insoluble in water

SPECIFIC GRAVITY: 2.65

Coef. Water/Oil Dist. N/A

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY:	Non flammable	MEANS OF EXTINGUISHMENT:	Non-combustible. May be used to extinguish fires.
FLASH POINT:	N/A	Hazardous Combustion Products:	None
Upper / lower Flam. Limit:	N/A		
AUTOIGNITION TEMP.:	N/A		

EXPLOSION DATA

Sensitivity to Impact:	None
Sensitivity to Static Discharge:	None

SECTION V - REACTIVITY DATA

CHEMICAL STABILITY:	Stable
INCOMPATIBILITY WITH OTHER SUBSTANCES:	ClF ₃ , MnF ₃ , OF ₂
HAZARDOUS POLYMERIZATION:	Will not occur
HAZARDOUS DECOMPOSITION PRODUCTS:	None

SECTION VI - HEALTH HAZARD DATA

The portion of each product that can be classified as respirable crystalline silica is described in the following section. The remainder of the material is not classified as a health hazard.

Symptoms of overexposure to crystalline silica

Inhaled: Shortness of breath, coughing, reduced pulmonary function.

Excessive inhalation of crystalline silica dust will result in respiratory disease, including silicosis, pneumoconiosis and pulmonary fibrosis.

Contact with eyes or skin: Eye irritation

Ingestion: May cause gastrointestinal discomfort.

Suspected cancer agent? Yes - respirable crystalline silica portion only.

Federal OSHA No

NTP Yes. Respirable Crystalline silica has been listed in the 6th Annual Report on Carcinogens.

IARC Yes. Monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Humans (Vol 68, 1997) concludes that there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the forms of quartz and cristobalite (Group 1) in certain industrial circumstances, but that carcinogenicity may be dependent on inherent characteristics of the crystalline silica or external factors affecting its biological activity or distribution if its polymorphs.

Medical Conditions Aggravated by Exposure

Individuals with pulmonary or respiratory disease should avoid exposure to dust.

First Aid Procedures See section IX

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Personal Protective Equipment:

Where the creation of dust is unavoidable, use conventional NIOSH approved or equivalent respiratory protection equipment based on considerations of airborne concentration and duration of exposure

Gloves: Impervious to moisture

Eye: Use appropriate eye protection to minimize contact with dust from dry product, or with wet product after mixing with water.

Other: Wear appropriate clothing and footwear for the specific application.
Clean clothing which has become dusty.

SECTION VIII - CONTROL MEASURES

Engineering Controls:

Use adequate ventilation. Do not permit dust to accumulate in work area.

Leak and Spill Procedure:

If uncontaminated, collect for reuse or disposal. Use dustless procedures. If contaminated, use appropriate method and container for contaminant.

SECTION VIII - continued

Waste Disposal:

If uncontaminated, dispose as a non-metallic mineral.

If contaminated, use appropriate method for contaminant in accordance with applicable regulation(s).

Handling Procedures and Equipment:

Avoid creation of respirable dust if possible. Use adequate ventilation and dust collection.

Avoid contact with wet product during use.

Storage Requirements:

Store in a dry place.

Special Shipping Information:

Protect from moisture.

SECTION IX - FIRST AID MEASURES

Eyes: Flush with running water for at least 15 minutes. Obtain medical attention.

Skin: Wash with soap and water. For caustic burns to skin, consult a doctor.

Ingestion: Drink large amounts of water. Do not induce vomiting. Seek immediate medical attention.

Gross Inhalation of Dust:

Remove to fresh air. Give oxygen with artificial respiration as needed. Obtain medical attention for treatment, observation and support as needed.

DISCLAIMER:

The information contained herein is based on data considered to be accurate. SANDLOCK makes no warranties express or implied and assumes no responsibility for the accuracy or completeness of the data. SANDLOCK further assumes no responsibility for personal injury or property damage to vendees, users, or third parties caused by this material. Such vendees or users assume all risks associated with the use of this material.