

MATERIAL SAFETY DATA SHEET

PAVE CHEM

SEALERS AND CLEANERS FOR HARDSCAPES

SILOXAGUARD (SILOXANE)

(Formerly "CLAYGUARD OR INVISIGUARD")

SECTION I – PRODUCT IDENTIFICATION

Manufacturer's Name:

Pave Tech
 P.O. Box 576
 Prior Lake, Minnesota 55372
 (952) 226-6400
 Fax: (952) 226-6406
 Toll Free: (800) 728-3832

Name: SILOXAGUARD**Class:** 55**CAS No.:** mixture**UN No.:** none

SECTION II – HAZARDOUS INGREDIENTS

No hazardous materials

SECTION III – PHYSICAL DATA

VOC: 51 g/L**APPEARANCE AND ODOR:** Milky white, no odor**BOILING POINT:** 100°C**VAPOR DENSITY:** 1**% VOLATILE:** 100%**SOLUBILITY IN WATER:** Water emulsion**WATER REACTIVE:** Not reactive**SPECIFIC GRAVITY:** 1.03

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Does not flash**EXTINGUISHING MEDIA:** Carbon Dioxide, dry chemical, or water.**UNUSUAL FIRE & EXPLOSION HAZARD:** Not considered a fire hazard when involved in a fire. Does not contribute any unusual hazards.

SECTION V – HEALTH HAZARD DATA

POSSIBLE ROUTES OF ENTRY: Inhalation**ACUTE AND CHRONIC OVEREXPOSURE:** **Skin:** no skin irritation is expected. **Eyes:** mildly irritating to the eyes. **Breathing:** mist may cause mild irritation to upper respiratory tract.**Ingestion:** none known.

FIRST AID PROCEDURES

EYE CONTACT: Immediately flush with clear water for 15 minutes. Seek additional medical treatment.**SKIN CONTACT:** Wash with soap and water. See a physician if irritation occurs.**INHALATION (Breathing):** Remove to fresh air.**INGESTION (Swallowing):** Do not induce vomiting. Dilute contents of stomach with 3 to 4 glasses of milk or water. Contact a physician.

SECTION VI – REACTIVITY DATA

INCOMPATIBILITY (Materials to avoid): Bases, acids, and oxidizers**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide, and silicon dioxide

SILOXAGUARD *(continued)*

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

RELEASE OR SPILL: Ventilate area, absorb with absorbent material, and place in proper waste disposal containers

WASTE DISPOSAL METHODS: In accordance with local, state, and federal regulations.

SECTION VIII – CONTROL MEASURES

Insure adequate ventilation. Wear water resistant rubber gloves, and chemical splash goggles. Mechanical exhaust is recommended. Positive pressure in interior of occupied buildings during exterior application. Wear impervious clothing and boots. Wash thoroughly with soap and water after using this product.

DISCLAIMER:

The information contained herein is based on data considered to be accurate. Pave Tech makes no warranties express or implied and assumes no responsibility for the accuracy or completeness of the data. Pave Tech further assumes no responsibility for personal injury or property damage to vendees, users, or third parties caused by this material. Such vendees or users assume all risks associated with the use of this material.